

Environmental Product Declaration for:

Glued down LVT according to EN ISO 10582

This EPD was produced on April 2, 2025 and refers to:

Kährs LT Dry Back

GENERAL INFORMATION

In this EPD glued down LVT according to EN ISO 10582 floor coverings are declared. The application of this EPD is restricted printed laminate polyvinyl chloride floor coverings produced by the members of the European Resilient Flooring Manufacturers' Institute (ERFMI). Data are based upon production during 2017 for the European market. Data have been provided by 9 companies of ERFMI which represent 75% of ERFMI members. The production sites are located in Europe and China.

The EPD was created according to the specifications as per /EN 16810/ and as per ISO 14025 and EN 15804+A1

PRODUCT

Product description / Product definition

Resilient floor coverings are an entire product family of flexible flooring solutions available in sheet, tiles and planks. It is classified in heterogeneous or homogeneous composition based on plastics, linoleum, cork or rubber. Resilient floor coverings can provide different functionalities (acoustic, static control, slip resistance, easy maintenance etc.) to match a wide range of domestic, commercial and industrial applications. It is available in an enormous range of patterns and colours fitting with inspiration and decorative needs.

Luxury Vinyl Tile (LVT) floor coverings are polyvinyl chloride heterogeneous floor coverings consisting of a wear layer and other compact layers which differ in composition and/or design and can contain reinforcement and are supplied in tile and plank form.

Floor covering is covered by the Construction Product Regulation (CPR). In accordance with the CPR a Declaration of Performance (DoP) of its Essential Characteristics according to EN 14041 and the related CE mark are mandatory when the product is sold in the EU.

Application

According to /EN ISO 10874/ the area of application for resilient floor coverings is indicated by use classes. The declared product group covers the use classes 23, 34 and 43.

Technical Data

The following table contains the construction data of the declared product group:

Constructional data

Name	Value	Unit
Product thickness	2.3	mm
Surface weight	3.6	kg/m ²
Product Form	tiles	-

The data given in the Declaration of performance apply.

Base Materials / Ancillary materials

The product group has the following composition:

- Additives 3%
- Filler 34%
- Plasticizer 10%
- Pigments <1%
- Polymers (PVC) 37%
- Auxiliaries <1%
- Lacquer <1%
- Flooring Recyclate (PVC) 16%

Reference service life

The service lifetime of a floor covering for a certain application on a floor is too widespread to give one common number. For this EPD model the reference service lifetime (RSL) is set to one year. This means that all impacts for the use phase are based on the cleaning and maintenance model for one year.

Depending on the area of use based on /EN ISO 10874/, the technical lifetime advised by the manufacturer and the estimated time on the floor by the customer, the service lifetime can be determined. The use phase impacts should be calculated with the foreseen service life to arrive at the total environmental impact /EN 16810/.

The use phase impacts of this declaration are calculated with the expected service life entered in the ERFMI online EPD calculator (www.erfmi.com).

LCA: CALCULATION RULES

Declared Unit

1m² of floor covering.

Declared Unit

Name	Value	Unit
Declared unit	1	m ²
Declared unit	3.6	kg/m ²
Conversion factor to 1 kg	0.2778	-

The declaration refers to an average product from 8 production sites of ERFMI members. The data have been weighted according to the annual square meters produced by each site. The life cycle impact assessment is conducted based on the vertical average.

System boundary

Type of EPD: cradle to grave.

Modules A1-A3 include processes that provide materials and energy input for the system, manufacturing and transport processes up to the factory gate, as well as waste processing.

Module A4 includes transport of the floor covering to the place of installation.

Module A5 includes the production of offcuts and adhesive for the installation of the floor covering, and incineration of offcuts and packaging material.

Module B2 is including provision of cleaning agent, energy and water consumption for the cleaning of the floor covering incl. waste water treatment. The LCA results in this EPD are declared for a 20-year usage.

Module C1 considers electricity supply for the deconstruction of the flooring.

Module C2 includes transportation of the postconsumer waste to waste processing.

End of life scenarios are declared for:

- 100% incineration in a waste incineration plant (WIP) (Scenario 1, C3/1)
- 100% landfilling (Scenario 2, C4/2)
- 100% recycling according to information from AgPR, (Arbeitsgemeinschaft PVC-Bodenbelag Recycling) (Scenario 3 - for the recycling scenario the end of waste state is reached after removal from the building)

Module D includes potential benefits from all net flows given in module A5 and C3 that leave the product boundary system after having passed the end-of-waste state in the form of recovery and/or recycling potentials. Module D is declared for each scenario separately.

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

As background database /GaBi ts/ is used.

LCA: SCENARIOS AND ADDITIONAL TECHNICAL INFORMATION

The following technical information is a basis for the declared modules.

Transport to the construction site (A4)

Name	Value	Unit
Transport distance (truck)	2000	km
Capacity utilisation (including empty runs)	85	%

Installation in the building (A5)

Name	Value	Unit
Material loss (installation waste)	4.5	%
Auxiliary (adhesive)	0.3	%

Biogenic carbon incorporated in the packaging material is released as CO₂ emissions in module A5.

Maintenance (B2) per year

Name	Value	Unit
Water consumption	0.003	m ³
Electricity consumption	0.55	kWh
Maintenance cycle (vacuum cleaning & wet cleaning)	156	number/a
Auxiliary (detergent)	0.04	kg

End of Life (C1-C4)

Name	Value	Unit
Energy recovery [100%, Scenario 1]	3.6	kg
Landfilling [100%, Scenario 2]	3.6	kg
Recycling [100%, Scenario 3]	3.6	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

For module D the potential benefits given in module A5 and C3 are declared. For waste incineration combustion in a WIP (R1 > 0.6) with energy recuperation is considered.

LCA: RESULTS

[illegible]

Product Stage			Construction Process Stage		Use Stage							End of Life Stage				Benefits and Loads Beyond the System Boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MND	X	MND	MND	MND	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT: 1 M² GLUED DOWN LVT (3.6 KG/M²)

[illegible]

RESULTS OF THE LCA - RESOURCE USE: 1 M² GLUED DOWN LVT (3.6 KG/M²)

[illegible]

RESULTS OF THE LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

1 M² GLUED DOWN LVT (3.6 KG/M²)

[illegible]

TOXICITY

For the calculation the USEtox model (Version 2.1) is used.

USEtox is officially endorsed by the UNEP/SETAC Life Cycle Initiative, and recommended as assessment method by the European Commission (EC) in the Recommendations on the Use of Common Methods to Measure and Communicate the Life Cycle Environmental Performance of Products and Organisations, 2013/179/EU, by the European Commission's Joint Research Centre – Institute for Environment and Sustainability (JRC-IES) in the International Reference Life Cycle Data System (ILCD) Handbook / USEtox® Documentation/.

The amendment to EN 15804 will consider USEtox as an additional optional indicator /EN 15804+A2/.

RESULTS OF THE LCA - TOXIC IMPACT: 1M ² INSTALLED												
		Manu-facturing	Installation		Use stage	End-of-Life				Potential benefits		
Parameter	Unit	A1-3	A4	A5	B2	C1	C2	C3/1	C4/2	D/1	D/2	D/3
ETP-fw	CTUe	2.19E-02	1.89E-03	2.38E-03	1.23E-2	2.12E-05	1.07E-04	1.01E-03	3.51E-04	-1.52E-03	-1.26E-04	-1.26E-04
HTP-c	CTUh	5.13E-09	1.73E-12	2.59E-10	2.38E-10	5.61E-13	1.05E-13	1.96E-11	1.74E-11	-1.25E-10	-9.78E-12	-9.78E-12
HTP-nc	CTUh	1.78E-09	7.27E-13	8.80E-11	1.21E-11	2.94E-14	5.08E-14	8.10E-13	4.31E-12	-3.30E-12	-2.65E-13	-2.65E-13
Caption	ETP-fw = Ecotoxicity; HTP-c = Human toxicity, cancer effects; HTP-nc = Human toxicity, non-cancer effects											

The results of these environmental impact indicators shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator /EN 15804+A2/.

REFERENCES

/IBU 2016/

IBU (2016): General Programme Instructions for the Preparation of EPDs at the Institut Bauen und Umwelt e.V., Version 1.1 Institut Bauen und Umwelt e.V., Berlin.
www.ibu-epd.com

/ISO 14025/

DIN EN /ISO 14025:2011-10/, Environmental labels and declarations - Type III environmental declarations - Principles and procedures

/EN 15804/

/EN 15804:2012-04+A1 2013/,
Sustainability of construction works - Environmental Product Declarations - Core rules for the product category of construction products

/PCR 2017, Part A/

Institut Bauen und Umwelt e.V., Berlin (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Background Report. 04/2017
www.ibu-epd.com

/PCR 2018, Part B/

Institut Bauen und Umwelt e.V., Berlin (pub.): Product Category Rules for Construction Products from the range of Environmental Product Declarations of Institut Bauen und Umwelt (IBU), Part B: Requirements on the EPD for floorcoverings, Institut Bauen und Umwelt e.V.,
www.ibu-epd.com, 02/2018

/EN 16810/

EN 16810: Resilient, textile and laminate floor coverings - Environmental product declarations - Product category rules, May 2017

/EN ISO 10582/

EN ISO 10582: Resilient floor coverings - Heterogeneous poly(vinyl chloride) floor coverings – Specification

/EN ISO 10874/

EN ISO 10874: Resilient, textile and laminate floor coverings - Classification (ISO 10874:2009)

/EN ISO 14041/

EN ISO 14041: Health, safety and energy saving requirements; EN 14041: Resilient, textile and laminate floor coverings - Essential characteristics

/GaBi ts/

GaBi ts dataset documentation for the software-system and databases, LBP, University of Stuttgart and thinkstep, Leinfelden-Echterdingen, 2017 (www.gabi-software.com/)

ILCD

International Reference Life Cycle Data System (ILCD) Handbook - Nomenclature and other provisions

USEtox

Rosenbaum, R.K., Bachmann, T.M., Gold, L.S., Huijbregts, M.A.J., Jolliet, O., Juraske, R., Köhler, A., Larsen, H.F., MacLeod, M., Margni, M., McKone, T.E., Payet, J., Schuhmacher, M., van de Meent, D., Hauschild, M.Z. (2008): USEtox -The UNEPSETAC toxicity model: recommended characterisation factors for human toxicity and freshwater ecotoxicity in Life Cycle Impact Assessment. International Journal of Life Cycle Assessment, 13(7): 532-546, 2008

USEtox® Documentation

Fantke, P., Bijster, M., Guignard, C., Hauschild, M., Huijbregts, M., Jolliet, O., Kounina, A., Magaud, V., Margni, M., McKone, T.E., Posthuma, L., Rosenbaum, R.K., van de Meent, D., van Zelm, R., 2017. USEtox® 2.0 Documentation (Version 1), <http://usetox.org>

EN 15804+A2

EN 15804:2012+A1:2013/FprA2:2019
Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products

EPD 2019

EPD of Cork floor tiles according to EN 12104, EPD-ERF-20180184-CCI1-EN, Institut Bauen und Umwelt e.V. (IBU)